

(19) World Intellectual Property Organisation
International Bureau



(43) International Publication Date
13 January 2005 (13.01.2005)


PCT

(10) International Publication Number
WO 2005/003733 A1

- (51) International Patent Classification⁷: G01N 1/20, 1/10, B01L 3/02
- (21) International Application Number: PCT/EP2004/006094
- (22) International Filing Date: 5 June 2004 (05.06.2004)
- (25) Filing Language: German
- (26) Publication Language: German
- (30) Priority Data: 103 30 299.9 4 July 2003 (04.07.2003) DE
- (71) Applicant (for all designated States except US): **MERCK PATENT GMBH** [DE/DE]; Frankfurter Strasse 250, 64293 Darmstadt (DE).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **SCHMELZ, Michael** [DE/DE]; Im Meerchen 21, 64560 Riedstadt (DE). **BRENNER, Günter** [DE/DE]; Jahnstrasse 37a, 64347 Griesheim (DE). **GREVE, Thomas** [DE/DE]; Rodgaustrasse 2c, 64291 Darmstadt (DE). **WURZIGER, Hanns** [DE/DE]; Greinstrasse 7b, 64291 Darmstadt (DE). **ARNDT, Mirco** [DE/DE]; Ludwigstrasse 26, 64367 Mühlthal (DE).
- (74) Common Representative: **MERCK PATENT GMBH**; Frankfurter Strasse 250, 64293 Darmstadt (DE).
- (81) Designated states (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG,

[continued overleaf]

(54) Title: SAMPLING DEVICE FOR A MICROREACTION SYSTEM



(57) Abstract: A sampling device (1) for a micro-reaction system (3) has an exit aperture (4) and an aperture a suction line (9) arranged laterally alongside the exit aperture (4), where a reduced pressure can be generated in the suction line (9) for aspiration of the substances (13) exiting from the exit aperture (4). The exit aperture (4) is designed in the form of a capillary and can be positioned relative to the aperture of the suction line (9). A housing (6) having an outlet aperture (14) for substances (13) exiting from the exit aperture (4) and having a passage aperture (8) for the suction line (9) is arranged around the exit aperture (4). The suction line (9) runs into a collecting vessel (10), which is connected via a magnetic valve (11) to a vacuum line (12).

KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZW.

FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

- (84) **Designated states** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.